

ToLEDo Micro-Lynx

TOLEDO MICROLYNX FROSTED 650LM 830 SL

0026810



Product features

- ToLEDo Microlynx LED is the perfect replacement for GX53 CFL lamp
- Compact design 15,000 hours rated life
- Higher lumen output
- Good colour rendering - CRI80
- Non-dimmable
- 3 years warranty
- Perfect for kitchen cabinets, showcases, display units and wardrobes



PRODUCT OVERVIEW

Product name	TOLEDO MICROLYNX FROSTED 650LM 830 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740840
Warranty	3 years
Luminous flux (lm)	650
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Wattage (W)	6.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288268101

DATA TABLE

General data

Product name	TOLEDO MICROLYNX FROSTED 650LM 830 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740840
Warranty	3 years

Optical data

Luminous flux (lm)	650
Luminous flux (Rated) (lm)	650

ToLEDo Micro-Lynx

TOLEDO MICROLYNX FROSTED 650LM 830 SL

0026810

Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	6.5
Equivalent watt (W)	51
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2.5
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	7
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	166
Max. Luminaires per 16A C Breaker	266
Max. Luminaires per 20A C Breaker	334

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	74.3
Nominal Product Diameter (mm)	25
Weight (kg)	0.048

Packaging

Single packaging type	Carton
Product EAN number	5410288268101
Packaging single length / height (cm)	7.6
Packaging single width (cm)	2.7
Packaging single depth (cm)	7.6
DUN14 (inner)	25410288268105
Units per inner package	6
DUN14 (outer)	15410288268108
Units per outer package	6
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	8.4

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No

ToLEDo Micro-Lynx

TOLEDO MICROLYNX FROSTED 650LM 830 SL

0026810

Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

