

ToLEDo Striplight V2

ToLEDo ST V2 300mm 3.5W 280lm S14s

0026851



Range Features

- Value for money.
- Easy retrofit for your bathroom and kitchen fixture.
- Energy saving incandescent retrofit LED lamp for shaver lighting and mirror lighting.
- Low power consumption to maximise energy saving potential.
- 15'000 hours life reducing maintenance costs.
- Existing in different length and caps (S15s,S19,S14s,S14d).
- 3 Year warranty.

PRODUCT OVERVIEW

Lamp finish	frosted
Lamp shape	Striplight
Colour temperature (K)	2700
CRI (Ra)	80
Dimmable	no
EAN code	5410288268514
Energy class	A+
Equivalent watt (W)	35
Cap/Base	S14s
Beam angle(°)	40
Type	ToLEDo Striplight
Watt (Nominal) (W)	3.5
Light colour	827 Homelight
Ordering number	0026851
Efficacy (Rated) (lm/w)	80
Average life (Rated) (h)	15000
Luminous flux (Rated) (lm)	280
Technology	LED
Voltage (V)	220-240
Colour consistency (SDCM)	6

DATA TABLE

General data

Average life (Nominal) (h)	15000
Control gear required	No
Lamp finish	frosted
Lamp shape	Striplight
Control gear availability	No
Dimmable	no

ToLEDo Striplight V2

ToLEDo ST V2 300mm 3.5W 280lm S14s

0026851

EAN code	5410288268514
Energy class	A+
Energy saving lamp	Yes
General application	Hospitality; Residential & Consumer
Intended purpose	General lighting
Cap/Base	S14s
Lamp mercury content (mg)	0
Type	ToLEDo Striplight
No. of switching cycles before premature failure (min)	50000
Optimal operating condition (°C)	25
Ordering number	0026851
Range features	<p>Value for money. Easy retrofit for your bathroom and kitchen fixture. Energy saving incandescent retrofit LED lamp for shaver lighting and mirror lighting. Low power consumption to maximise energy saving potential. 15'000 hours life reducing maintenance costs. Existing in different length and caps (S15s,S19,S14s,S14d). 3 Year warranty.</p>
Product name	ToLEDo ST V2 300mm 3.5W 280lm S14s
Average life (Rated) (h)	15000
Special purpose lamp	No
Starting time (max) (s)	0.05
Technology	LED
Transformer required	No
Sales pack quantity	6
Warm-up time to 60% of full light (max) (s)	< 1s => 60%

Optical data

Chromaticity coordinate X	-1
Chromaticity coordinate Y	-1
Colour temperature (K)	2700
CRI (Ra)	80
Beam angle(°)	40
Light colour	827 Homelight
Lumen maintenance at end of nominal life (%)	70
Luminous flux (Nominal) (lm)	280
Peak intensity (cd)	700
Luminous flux (Rated) (lm)	280
Suitable for accent lighting	no
Colour Consistency	6
Beam angle (Rated) (°)	40

ToLEDo Striplight V2

ToLEDo ST V2 300mm 3.5W 280lm S14s

0026851

Adjustable chromaticity	no
Colour consistency (SDCM)	6

Electrical data

Current (A)	29
Equivalent watt (W)	35
kWh per 1000 hours burning time	4
Lamp power factor	0.5
Watt (Nominal) (W)	3.5
Efficacy (Rated) (lm/w)	80
Watt (Rated) (W)	3.5
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	300
Single packaging type	Blister
Weight (kg)	0.05
Lamp dimension equal to filament lamp equivalent	yes
Designed for optimum use in non standard conditions	No
Fluorescent lamp replacement	no
Inner package net weight (kg)	0.30
Inner package dimensions (L x W x H) (cm)	22.00 x 16.00 x 6.00
Outer package dimensions (L x W x H) (cm)	39.00 x 24.50 x 35.00
Single package dimensions (L x W x H) (cm)	14.00 x 12.00 x 5.50

TECHNICAL DRAWINGS



ToLEDo Striplight V2

ToLEDo ST V2 300mm 3.5W 280lm S14s

0026851

