

## Inset Trend 75 Swing IP44 Indoor

INSET TREND SW IP44 OUTD AN EX LMP

**3099390**



### Range features

- 2 x 25° Tiltable Square IP44 75mm cut out accent down light with multiple colour finishes and easy lamp replacement system with added non corrosive finish for outdoor applications

## PRODUCT OVERVIEW

|                         |                           |
|-------------------------|---------------------------|
| Ordering number         | 3099390                   |
| Technology              | LED/Halogen               |
| EAN code                | 8711971993902             |
| Mount                   | Ceiling recessed          |
| Housing                 | Die Cast Aluminium        |
| CRI (Ra)                | Dependent on lamp         |
| LOR (%)                 | Dependent on lamp         |
| Beam angle(°)           | Dependant on light source |
| Efficacy (Rated) (lm/w) | Dependent on lamp         |
| Voltage (V)             | Dependent on lamp         |
| Colour                  | Anthracite                |
| IP rating               | IP44                      |
| IK rating               | 2                         |

## Inset Trend 75 Swing IP44 Indoor

INSET TREND SW IP44 OUTD AN EX LMP

3099390

## DATA TABLE

## General data

|                            |  |
|----------------------------|--|
| Ordering number            | 3099390  |
| Technology                 | LED/Halogen  |
| Average life (Nominal) (h) | Dependent on light source  |
| EAN code                   | 8711971993902  |
| Mount                      | Ceiling recessed   |
| Range features             | 2 x 25° Tilttable Square IP44 75mm cut out accent down light with multiple colour finishes and easy lamp replacement system with added non corrosive finish for outdoor applications |
| Product name               | INSET TREND SW IP44 OUTD AN EX LMP   |
| Environment                | Interior/Exterior  |
| Housing                    | Die Cast Aluminium   |

## Optical data

|                   |                           |
|-------------------|---------------------------|
| CRI (Ra)          | Dependent on lamp         |
| LOR (%)           | Dependent on lamp         |
| Beam angle (°)    | Dependant on light source |
| Distribution type | Direct                    |
| Glare control     | Dependant on light source |

## Electrical data

|                             |                   |
|-----------------------------|-------------------|
| Efficacy (Rated) (lm/w)     | Dependent on lamp |
| Total power consumption (W) | Dependent on lamp |
| Voltage (V)                 | Dependent on lamp |
| Drive current (mA)          | Dependent on lamp |

## Physical data

|                                      |                           |
|--------------------------------------|---------------------------|
| Maximum distance from luminaire (cm) | 100                       |
| Colour                               | Anthracite                |
| Lamp included                        | No                        |
| Height (mm)                          | 100                       |
| Width (mm)                           | 95                        |
| Length (mm)                          | 95                        |
| IP rating                            | IP44                      |
| IK rating                            | 2                         |
| Vertical tilt (°)                    | 25                        |
| Cutout diameter (mm)                 | 75                        |
| Cutout length (mm)                   | 75                        |
| Cutout shape                         | Round                     |
| Recessed depth (mm)                  | 100                       |
| Diffuser finish                      | Dependant on light source |
| Diffuser material                    | Dependant on light source |
| Reflector finish                     | Dependant on light source |

**Inset Trend 75 Swing IP44 Indoor**

*INSET TREND SW IP44 OUTD AN EX LMP*

**3099390**

---